

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 March 2001 (15.03.2001)

PCT

(10) International Publication Number
WO 01/18246 A1

(51) International Patent Classification⁷: C12Q 1/68.
G01N 33/53, C12M 1/00, 1/42, C07H 21/02, 21/00, B01L
3/00

NOTTERMAN, Dan [US/US]; 19 Foxcroft Drive, Prince-
ton, NJ 08540 (US). LANDWEBER, Laura, F. [US/US];
38 Chestnut Street, Princeton, NJ 08540 (US).

(21) International Application Number: PCT/US00/23652

(74) Agents: COLLINS, Bruce, M. et al.; Mathews, Collins,
Shepherd & Gould, P.A., Suite 306, 100 Thanet Circle,
Princeton, NJ 08540-3684 (US).

(22) International Filing Date: 28 August 2000 (28.08.2000)

(25) Filing Language: English

(81) Designated States (national): JP, US.

(26) Publication Language: English

(84) Designated States (regional): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE).

(30) Priority Data:
60/150,899 26 August 1999 (26.08.1999) US
60/211,063 13 June 2000 (13.06.2000) US

Published:
— with international search report

(71) Applicant (for all designated States except US): THE
TRUSTEES OF PRINCETON UNIVERSITY [US/US];
Princeton University, P.O. Box 36, Princeton, NJ
08544-0036 (US).

(48) Date of publication of this corrected version:
6 December 2001

(72) Inventors; and
(75) Inventors/Applicants (for US only): SOHN, Lydia, Lee
[—/US]; 5 Campbell Woods Way, Princeton, NJ 08540
(US). SALEH, Omar, A. [US/US]; 4 Chestnut Street,
Princeton, NJ 08540 (US). KNIGHT, James, Bradford
[US/US]; 214 Fisher Place, Princeton, NJ 08540 (US).

(15) Information about Correction:
see PCT Gazette No. 49/2001 of 6 December 2001, Section
II

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: MICROFLUIDIC AND NANOFUIDIC ELECTRONIC DEVICES FOR DETECTING CHANGES IN CAPACITANCE OF FLUIDS AND METHODS OF USING

(57) Abstract: The present invention relates to microfluidic and nanofluidic devices for detecting or measuring an electrical property of a fluid including a liquid or aerosol, a single molecule or a single particle or cell in a fluid. In a particular embodiment, the devices detect or measure changes in capacitance of a fluid, molecule, particle or cell as it passes through the device. The present invention also relates to the detection and measurement of single molecules, in particular, biological molecules. The present invention also relates to methods of sequencing polynucleotide molecules, such as RNA or DNA, by detecting differentially labeled single nucleotides. Applications of this technology of single molecule detection, includes DNA or RNA sequencing which require a resolution of 3-5 nucleotides, detection of SNPs which require a single nucleotide resolution, proteomics which require 3 nucleotide resolution, and particle sizing. The microfluidic device can be used to determine the DNA content of cell, to analyze cell-cycles kinetics of populations of cells and as an assay for abnormal changes in DNA content of cells. The nano-microfluidic devices of this invention also have utility for use as detectors in molecular sorting systems and detecting of pathogens and spores. The present invention is also referred to as "Capacitance cytometry".

WO 01/18246 A1